

Pole Transportation Safety Systems & Lighting LED Pole Mount & Flag Holder

1-419-331-0371
1-800-874-4702
www.aircraftdynamics.com



Cat. No. 7015

Includes LED Light System, Batteries & Two Flags.

Using highly effective, long lasting LED technology - LED is rated for 100,000 hours of heavy duty operation - this system provides the ultimate in pole mount safety. The single bright red LED, with a 5-7 mile visibility range, includes four flash patterns: Comet, Single, Steady Burn and Flare Flicker. Light module is encapsulated for vibration and moisture resistance with dual front/angled reflectors. System is powered by three alkaline "C" batteries, providing 100+ hours of continuous operation. Easy to attach and deploy, using heavy duty strap that attaches to all pole sizes. Additional features include powder coated metal components & dual flag holders. Kit includes batteries and two flags.



LED Pole Lighting Specifications:


Light ----- LED: Four Flash Patterns
LED Rating ----- 100,000 hours
Batteries ----- Three Alkaline "C"s
Battery Run Time ----- 100+ Hours
Color Options ----- Red

IMPORTANT SAFETY AND OPERATING INSTRUCTIONS

1) MOUNTING




Always use strap provided with light. Make sure strap is properly and tightly secured.
WARNING: Never use light if strap is damaged or frayed in any manner. If damaged or frayed contact Aircraft Dynamics for replacement. Part No. 7349 Strap.



Light contains 3 holes for securing light to pole. Use nails or screws when mounting to the pole. **WARNING:** Light may shift toward end of pole during transportation. Use holes with screws or nails to properly secure light.

2) OPERATION

All functions of the LED Pole light are activated using the control button. Activate the unit by pressing the control button. Activation is as follows:
OFF > Mode 1 (Flare Flicker); Mode 2 > (Single Flash); Mode 3 > (Comet Flash); Mode 4 > (Steady On) > OFF



3) LOW BATTERY INFORMATION

Battery life is significantly effected by cold temperatures. For best results at temperatures below 32 degrees F, store the unit between 45 degrees and 75 degrees F when not in use. NOTE: Storing batteries at temperatures above 90 degrees F will shorten their shelf life.


This unit has been designed to alert users if a low battery condition exists. If the user tries to activate the unit when a low battery condition has been detected, the unit will produce a single flash and then turn off. Subsequent attempts to activate the unit will produce the same results.

If a low battery condition is detected while the unit is in operation, the current display mode will be replaced with a unique 'alert' mode. No other display modes are available.

If the unit exhibits either of these behaviors, immediately replace all 3 batteries.

To replace the batteries, remove the 3 screws that secure the top cover to the bottom base. With these screws removed, lift the cover off the base and set aside. Do not subject the wire connecting the battery holder to the LED circuit board to unnecessary strain.

Remove screws and cover to replace batteries. Size: C Alkalines'
DO NOT USE RECHARGEABLE BATTERIES IN THIS PRODUCT!



WARRANTY INFORMATION

THE MANUFACTURER WARRANTS TO THE ORIGINAL PURCHASER ONLY, THAT THIS PRODUCT WILL BE FREE OF DEFECTS IN MATERIAL AND WORKMANSHIP FOR A PERIOD OF ONE (1) YEAR FROM THE DATE OF PURCHASE. LIABILITY HEREUNDER IS LIMITED TO REPLACEMENT OF THE PRODUCT OR REPAIR OF THE PRODUCT. REPLACEMENT OR REPAIR IS AT THE DISCRETION OF THE MANUFACTURER. THIS WARRANTY IS VOID IF THE PRODUCT HAS BEEN DAMAGED BY ACCIDENT, UNREASONABLE USE, NEGLIGENCE, MISUSE, TAMPERING OR OTHER CAUSES NOT ARISING FROM DEFECTS IN MATERIAL OR WORKMANSHIP. THIS WARRANTY EXTENDS TO THE ORIGINAL PURCHASER OF THE PRODUCT ONLY.

DURING THE WARRANTY PERIOD ABOVE, YOUR PRODUCT WILL BE REPLACED WITH A COMPARABLE PRODUCT, OR REPAIRED, IF THE PRODUCT IS RETURNED, POSTAGE PREPAID, TO THE MANUFACTURER TOGETHER WITH PROOF OF PURCHASE DATE AND BY FIRST OBTAINING A RETURN AUTHORIZATION NUMBER FROM THE COMPANY. IF A RETURN AUTHORIZATION IS GRANTED, PLEASE INCLUDE A NOTE DESCRIBING THE PROBLEM WHEN YOU RETURN THE UNIT. THE REPLACED OR REPAIRED PRODUCT WILL BE IN WARRANTY FOR THE REMAINDER OF THE ORIGINAL WARRANTY PERIOD. OTHER THAN COST OF SHIPPING THE PRODUCT TO THE MANUFACTURER, NO CHARGE WILL BE MADE FOR REPAIR OR REPLACEMENT OF THE PRODUCT.