


WS 5/WS 5A End Stripper

800-874-4702

www.aircraftdynamics.com



BUSHING SELECTION TABLE

These tables should only be used as a guide.
Utility Division - Aircraft Dynamics Corporation

| Cable O.D. to be stripped | | Bushing # | Cable O.D. to be stripped | | Bushing # |
|---------------------------|---------------|-----------|---------------------------|---------------|------------|
| (inch) | (mm) | | (inch) | (mm) | |
| .260 - .285 | 6.60 - 7.24 | WS 5-.300 | .761 - .785 | 19.33 - 19.94 | WS 5-.800 |
| .286 - .310 | 7.26 - 7.87 | WS 5-.325 | .786 - .810 | 19.96 - 20.57 | WS 5-.825 |
| .311 - .335 | 7.90 - 8.51 | WS 5-.350 | .811 - .835 | 20.60 - 21.21 | WS 5-.850 |
| .336 - .360 | 8.53 - 9.14 | WS 5-.375 | .836 - .860 | 21.23 - 21.84 | WS 5-.875 |
| .361 - .385 | 9.17 - 9.78 | WS 5-.400 | .861 - .885 | 21.87 - 22.48 | WS 5-.900 |
| .386 - .410 | 9.80 - 10.41 | WS 5-.425 | .886 - .910 | 22.50 - 23.11 | WS 5-.925 |
| .411 - .435 | 10.44 - 11.05 | WS 5-.450 | .911 - .935 | 23.14 - 23.75 | WS 5-.950 |
| .436 - .460 | 11.07 - 11.68 | WS 5-.475 | .936 - .960 | 23.77 - 24.38 | WS 5-.975 |
| .461 - .485 | 11.71 - 12.32 | WS 5-.500 | .961 - .985 | 24.41 - 25.02 | WS 5-1.000 |
| .486 - .510 | 12.34 - 12.95 | WS 5-.525 | .986 - 1.010 | 25.04 - 25.65 | WS 5-1.025 |
| .511 - .535 | 12.98 - 13.59 | WS 5-.550 | 1.011 - 1.035 | 25.67 - 26.29 | WS 5-1.050 |
| .536 - .560 | 13.61 - 14.22 | WS 5-.575 | 1.036 - 1.060 | 26.31 - 26.92 | WS 5-1.075 |
| .561 - .585 | 14.25 - 14.86 | WS 5-.600 | 1.061 - 1.085 | 26.95 - 27.56 | WS 5-1.100 |
| .586 - .610 | 14.88 - 15.49 | WS 5-.625 | 1.086 - 1.110 | 27.58 - 28.19 | WS 5-1.125 |
| .611 - .635 | 15.52 - 16.13 | WS 5-.650 | 1.111 - 1.135 | 28.22 - 28.83 | WS 5-1.150 |
| .636 - .660 | 16.15 - 16.76 | WS 5-.675 | 1.136 - 1.160 | 28.85 - 29.46 | WS 5-1.175 |
| .661 - .685 | 16.79 - 17.40 | WS 5-.700 | 1.161 - 1.185 | 29.49 - 30.10 | WS 5-1.200 |
| .686 - .710 | 17.42 - 18.03 | WS 5-.725 | 1.186 - 1.210 | 30.12 - 30.73 | WS 5-1.225 |
| .711 - .735 | 18.06 - 18.67 | WS 5-.750 | 1.211 - 1.235 | 30.76 - 31.37 | WS 5-1.250 |
| .736 - .760 | 18.69 - 19.30 | WS 5-.775 | 1.236 - 1.260 | 31.39 - 32.00 | WS 5-1.275 |
| | | | 1.261 - 1.285 | 32.03 - 32.64 | WS 5-1.300 |